

VX-230 Series

VHF/UHF Portable Radios

SPECIFICATION SHEET

The Essential Radio for General Communications

Get cost-effective communications with the VX-230 radio that delivers more features and performance in its class for maximum return on investment.

Easy to Carry

A radio that won't get in the way, the VX-230 is compact and lightweight without sacrificing the performance and reach needed on the job.

Battery Power Options For Every Budget

Designed to use powerful Li-Ion and Ni-MH battery technology with three options providing up to 9 hours to 16.5 hours of operation with the battery saver enabled.

Safety Features Not Sacrificed

As with all Vertex Standard portable radios, the VX-230 includes both Emergency and Lone Worker alert functions to help monitor user safety. The Emergency alert can be programmed to instantly notify help with a press of a button. The Lone Worker function allows supervisors to monitor the safety status of radio users working alone in isolated areas.

More Scanning Options

While many radios provide one or two scanning options, the VX-230 radio has four scanning options for greater convenience and flexibility in the way you need your radios to perform. Options include: Priority, Dual Watch, Follow Me and Talk Around scan.

Exclusive Auto-Range Transponding System – ARTS™

Only Vertex Standard radios are designed to inform you when you and another ARTS™-equipped station are within communication range. If out of range, your radio senses no signal has been received and beeps to alert you. A great solution to keep your workers coordinated.



Top

Side

110 (H) x 58 (W) x 30 (D) mm

The Vertex Standard Difference

Our number one goal is achieving superior customer satisfaction by delivering products and services that exceed your expectations. Count on Vertex Standard for radios that are built to last and designed to provide more features for a better return on your investment. Ask your Dealer for more details.

VX-230 Series

VHF/UHF Portable Radios



SPECIFICATION SHEET

www.vertexstandard.com/ap

Additional Features

- ▶ 16 channel capacity
- ▶ Two programmable keys
- ▶ Battery power save
- ▶ Emergency
- ▶ Lone Worker
- ▶ DTMF ANI
- ▶ DTMF Speed Dial
- ▶ 2-Tone Encode and Decode
- ▶ CTCSS / DCS Encode and Decode
- ▶ Manual squelch adjustment
- ▶ Radio-to-radio cloning

Accessories

- ▶ MH-450S: Speaker microphone
- ▶ MH-360S: Compact speaker microphone
- ▶ MH-45B4B: Noise canceling speaker microphone
- ▶ MH-37A4B: Earpiece microphone
- ▶ VH-115S: Behind-the-head headset with boom mic
- ▶ VH-215S: Over-the-head single-muff headset
- ▶ VC-25: Over-the-head VOX headset
- ▶ FNB-132LI: 2300 mAh Li-Ion battery
- ▶ FNB-V104LIA: 2300 mAh Li-Ion battery
- ▶ FNB-V106: 1200 mAh Ni-MH battery
- ▶ FNB-V131LI: 1380mAh Li-Ion battery
- ▶ FNB-V103LIA: 1380 mAh Li-Ion battery
- ▶ VAC-UNI : Desktop rapid charger (Li-Ion only)
- ▶ VAC-300: Desktop rapid charger (Li-Ion only)
- ▶ VAC-20: Desktop charger (FNB-V106)
- ▶ DCM-1: Desktop charger mounting adapter
- ▶ VCM-2: Vehicle charger mounting adapter
- ▶ VAC-6020: 6-unit charger (FNB-V106)
- ▶ VAC-6300: 6-Unit multi rapid charger (Li-Ion only)
- ▶ LCC-350: Leather case
- ▶ LCC-350S: Leather case with swivel belt clip
- ▶ CLIP-18: Belt clip
- ▶ CLIP-17E: Swivel belt clip

VX-230 Specifications

	VHF	UHF
General Specification		
Frequency Range	134 - 174 MHz	400 - 470 MHz, 450 - 520 MHz
Number of Channels	16	
Power Supply Voltage	7.4V DC ± 20%	
Channel Spacing	12.5 / 20* / 25* kHz	
PLL Steps	2.5 / 5 / 6.25 kHz	5 / 6.25 kHz
Battery Life (5-5-90 duty)	9.0 hours (w/saver) / 7.3 hours	
1200 mAh FNB-V106		
1380 mAh FNB-V131LI-UNI 1380 mAh FNB-V103LIA	10.8 hours (w/saver) / 8.8 hours	
2300 mAh FNB-V132LI-UNI 2300 mAh FNB-V104LIA	19.0 hours (w/saver) / 15.5 hours	
IP Rating	IP 54	
Operating Temperature Range	-22°F to +140°F (-30°C to +60°C)	
Frequency Stability	±2.5 ppm	
RF Input-Output Impedance	50 Ohms	
Dimension (H x W x D)	4.3 x 2.3 x 1.4 inches (110 x 58 x 36 mm) 2300 mAh battery options 4.3 x 2.3 x 1.2 inches (110 x 58 x 30 mm) 1380 mAh battery options	
Weight (Approx.) with Antenna, Belt Clip	11.6 oz (329 g) FNB-V132LI-UNI 11.5 oz (326 g) FNB-V104LIA 11.6 oz (288 g) FNB-V113LI-UNI 11.6 oz (287 g) FNB-V103LIA	

Receiver Specification: measured by TIA/EIA-603

Sensitivity 12dB SINAD	0.25 µV typical
Adjacent Channel Selectivity	65 / 60 dB 25 kHz / 12.5 kHz
Intermodulation	65 / 60 dB 25 kHz / 12.5 kHz
Spurious and Image Rejection	65 dB
Audio Output	500 mW @ 4 Ohms, 5% THD

Transmitter Specification: measured by TIA/EIA-603

Output Power	5 / 1 Watt
Modulation	16K0F3E, 11K0F3E
Conducted Spurious Emissions	65 dB below carrier
FM Hum and Noise	45 / 40 dB 25 kHz / 12.5 kHz
Audio Distortion	< 3 % @1 kHz

Applicable MIL-STD

Standard	Methods/Procedures			
	MIL 810C	MIL 810D	MIL 810E	MIL 810F
Low Pressure	500.1 / I	500.2 / I, II	500.3 / I, II	500.4 / I, II
High Temperature	501.1 / I	501.2 / I, II	501.3 / I, II	501.4 / I, II
Low Temperature	502.1 / I	502.2 / I	502.3 / I, II	502.4 / I, II
Temperature Shock	503.1 / I	503.2 / I	503.3 / I	503.4 / I, II
Solar Radiation	505.1 / I	505.2 / I Cat. AI	505.2 / I Cat. AI	505.4 / I Cat. AI
Rain	506.1 / I, II	506.2 / I, II	506.3 / I, II	506.4 / I, III
Humidity	507.1 / I, II	507.2 / II, III	507.3 / II, III	507.4 / I
Salt Fog	509.1 / I	509.2 / I	509.3 / I	509.4 / I
Dust	510.1 / I	510.2 / I	510.3 / I	510.4 / I, III
Vibration	514.2 / X	514.3 / I Cat. 10	514.4 / I Cat. 10	514.4 / I Cat. 24
Shock	516.2 / I, II, V	516.3 / I, IV	516.4 / I, IV	516.5 / I, IV

Specifications are subject to change without notice or obligation.

VERTEX STANDARD is registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. © Vertex Standard Co. Ltd. 2013

NSS230_10/2013